


OASIS LED PANEL LIGHT TYPE VERTICAL (Recessed T-Bar Ceiling - Imperial Size)
MODEL: YOS PV24/R


powered by

TRIDONIC
Specifications & Technical Data
Luminaires:

- Frame is Extruded From Aluminium (*White*)
- Mild Steel Housing (*Thickness 0.5mm*)
- Electrostatically Polyester Powder Coated
- Polycarbonate **Opal** Diffuser
- Nylon Connecting Devices
- Separate Mild Steel Gear Box
- Recessed T-Bar Ceiling
(*Imperial Size*)

Areas of Application:


Home, Hospitality, Hotels, Offices,
Retail, Supermarkets, Restaurants,
Shop Lighting, Storage Room,
Public & Commercial Building

Optional:

VITALITE VECK 36LED
≥ 2 Hours Duration Emergency Powerpack


Replace:

4x36W T8 FL & Save Over 50% On Energy



Model	System Lumens (lm)	System Power (W)	System Current (A)	Beam Angle (°)	LED Square Module (DC)	TRIDONIC LED Driver (THD < 20%) (AC 220-240V, 50/60Hz, PF 0.90)	Dimension (mm)		
							L	W	H
YOS PV24/R	8600lm	62W	0.26A	110°	4 x PV-SQ-128-xxxxK-G2	1 x LC 62/700-1400/57 flexC SC SNC4 (<i>Dip-Switch Set to 1200mA</i>)	1215	605	54

LED Square Module (DC)	Current (mA)	Luminous Flux (lm)	Power (W)	Voltage (V)	CCT (K)			CRI (Ra)	SDCM	Max. Temp. at tc (°C)	Lifespan (Hrs)
PV-SQ-128-xxxxK-G2 (SMD 2835 8C16B)	650mA	2600lm	15.1W	23.2V	3000K	4000K	6500K	≥ 80	≤ 5	80°C	50000Hrs
	700mA	2800lm	16.4W	23.4V	3000K	4000K	6500K	≥ 80	≤ 5	80°C	50000Hrs

Photometric Data


Flux Out: 2397 lm

Height (M)	Lux	CM
1	2289	115
2	572	231
3	254	346
4	143	462
5	92	577

Height Angle: 60° Diameter