

T8 LED Bare Batten Fitting c/w Mirror Angle Reflector
Model: OS YBC 2x1200mm + MIR 240A

Specifications & Technical Data

- Housing is Fabricated From Mild Steel (*Thickness 0.5mm*)
- Anodized Aluminium Mirror Angle Reflector (*Thickness 0.3mm*)
- Finished With Powder Electrostatically
- Stove-Coated With High Reflectivity White Epoxy
- Lampholder of Polycarbonate & Bronze
- Twist-Lock Lampholder For Reliable Contact
- Pre-Connected With 105°C HR PVC Wire
- Connecting Devices of Nylon 3 Way x 2.5mm²
- Degree of Protection: **IP20**
- Type of Protection: Class 1
- Mounting Method: Surface Ceiling / Wall / Suspension

Optional:

VITALITE VECK 18/T8 LED



3 Hours Duration Emergency Powerpack

SSR - Suspension Rod

• SSR 305 (305mm / 12")

• SSR 460 (460mm / 18")

• SSR 610 (610mm / 24")



Model	Luminaires					Dimension - mm			Current (A)	P.F. (λ)
	No. of Lamp	Power	Beam Angle	Reflector	Base	L	W	H	± 5 %	>
OS YBC 2x1200mm + MIR 240A	2	2 x 14W	130°	Anodized Aluminium	G13	1222	144	174	0.12	> 0.90

Lamp (AC Input 100-240V, 50/60Hz, Athd < 15%) (4ft)											
Brand	Code	Type	Base	Lumens (lm)	Power (W)	CCT (K)	CRI (Ra)	SDCM	Current	P.F.	Lifespan (Hrs)
TOSHIBA	T8 LEDtube PRO 1200mm 14W 4000K (RLDL0284C1440G1EX1)	T8 LED	G13	2100lm	14W	4000K	≥ 80Ra	≤ 6	0.06	> 0.9	50000Hrs
TOSHIBA	T8 LEDtube PRO 1200mm 14W 6500K (RLDL0284C1465G1EX1)	T8 LED	G13	2100lm	14W	6500K	≥ 80Ra	≤ 6	0.06	> 0.9	50000Hrs

Photometric Data